



Solatube 290/300 DS Integrated LED Light Kit P/N: 524290



Solatube 330/750 DS Integrated LED Light Kit P/N: 524330

OVERVIEW

- Daylight and LED combined in one ceiling fixture
- Dimmable LED
- 0-10V Controller options control LED to supplement daylight output
- High Efficacy LED - Lumens/Watt >100
- This minimalist ceiling fixture transitions seamlessly from day to nighttime use.
- Delivers 3,250 to 10,000 lumens
- Color temperature 4000K
- CRI 80

Solatube 290 DS and 300 DS LED P/N: 524290

LED	3,250 Lumens / 4000K
Color Rendering Index (CRI)	80
Driver	25W Meanwell Driver
Dimming Control	0-10v Sourcing, 10V PWM or Resistance
Ambient Working Temperature	Min= -40°C (-40°F) Max=55°C (131°F)
A/C Input Range	100-240V, 0.31A, 50/60Hz 277~, 0.12A, 50/60 Hz
Surge Protection	4KV/Line-Line 6KV/Line-Earth
Max Watts	25
Lumen /Watt	130
LED Heat Sink	Passive
LED Rated Hours	50,000 Hours

Solatube 330 DS and 750 DS LED P/N: 524330

LED	10,000 Lumens / 4000K
Color Rendering Index (CRI)	80
Driver	75W Meanwell Driver
Dimming Control	0-10v Sourcing, 10V PWM or Resistance
Ambient Working Temperature	Min= -40°C (-40°F) Max=55°C (131°F)
A/C Input Range	100-240V, 1.1A, 50/60Hz 277~, 0.5A , 50/60 Hz
Surge Protection	4KV/Line-Line 6KV/Line-Earth
Max Watts	75
Lumen /Watt	130
LED Heat Sink	Active
LED Rated Hours	50,000 Hours

COMPLIANCE

- cTUV_{us} Listed
- FCC compliant Part 15
- For indoor use only
- Suitable for damp locations



- To be installed with Solatube Daylighting Systems of compatible size only.
- Not intended for use in emergency fixtures or emergency lights.
- **⚠ CA RESIDENTS WARNING:** Cancer and Reproductive Harm—www.p65warnings.ca.gov

WARRANTY

- 5 Year Warranty