



Solatube 290/300 DS Integrated LED Light Kit P/N:
 524290—4000K (80 CRI)
 524240—4000K (90 CRI)
 524235—3500K (90 CRI)
 524230—3000K (90 CRI)



Solatube 330/750 DS Integrated LED Light Kit P/N:
 524330—4000K (80 CRI)
 524740—4000K (90 CRI)
 524735—3500K (90 CRI)
 524730—3000K (90 CRI)

NOTE: For lumen output of installed LED system, see IES files located at www.solatube.com/technical-resources/daylighting-photometric-ies

OVERVIEW

- Daylight and LED combined in one ceiling fixture
- 3 in 1 dimming function 0 ~ 10VDC. Dimming range 10-100%
- 0-10V controller options control LED to supplement daylight output
- High efficacy LED - Lumens/Watt >100
- This minimalist ceiling fixture transitions seamlessly from day to nighttime use.
- Delivers 2,800 to 10,000 lumens
- Available color temperatures—4000K, 3500K, 3000K

Solatube 290 DS and 300 DS LED

LED	3000K ≈ 2811 Lumens (90 CRI) 3500K ≈ 2913 Lumens (90 CRI) 4000K ≈ 3014 Lumens (90 CRI) 4000K ≈ 3522 Lumens (80 CRI)
Color Rendering Index (CRI)	80—90
Driver	25W Meanwell Driver
Dimming Control	0-10v Sourcing, 10V PWM or Resistance
Ambient Working Temperature	Min= -40°C (-40°F) Max=55°C (131°F)
A/C Input Range	100-240V, 0.31A, 50/60Hz 277~, 0.12A, 50/60 Hz
Surge Protection	4KV/Line-Line 6KV/Line-Earth
Max Watts	25
Lumen /Watt	3000K ≈ 128 (90 CRI) 3500K ≈ 133 (90CRI) 4000K ≈ 138 (90 CRI) 4000K ≈ 161 (80 CRI)
LED Heat Sink	Passive
LED Rated Hours	50,000 Hours

Solatube 330 DS and 750 DS LED

LED	3000K ≈ 10,333 Lumens (90 CRI) 3500K ≈ 10,708 Lumens (90 CRI) 4000K ≈ 10,932 Lumens (90 CRI) 4000K ≈ 11,932 Lumens (80 CRI)
Color Rendering Index (CRI)	80—90
Driver	75W Meanwell Driver
Dimming Control	0-10v Sourcing, 10V PWM or Resistance
Ambient Working Temperature	Min= -40°C (-40°F) Max=55°C (131°F)
A/C Input Range	100-240V, 1.1A, 50/60Hz 277~, 0.5A, 50/60 Hz
Surge Protection	4KV/Line-Line 6KV/Line-Earth
Max Watts	75
Lumen /Watt	3000K ≈ 138 (90 CRI) 3500K ≈ 143 (90 CRI) 4000K ≈ 146 (90 CRI) 4000K ≈ 162 (80 CRI)
LED Heat Sink	Active
LED Rated Hours	50,000 Hours

COMPLIANCE

- cTUV_{us} Listed
- FCC compliant Part 15
- For indoor use only
- Suitable for damp locations



- To be installed with Solatube Daylighting Systems of compatible size only.
- Not intended for use in emergency fixtures or emergency lights.
- **⚠ CA RESIDENTS WARNING:** Cancer and Reproductive Harm—
www.p65warnings.ca.gov

WARRANTY - 5 Year Warranty