

**SOLATUBE 330DS-C-DA-FC-AK-ES-TM-D  
(21 IN / 530 MM)  
CURB CAP  
SUSPENDED CEILING WITH  
SOFTLIGHT EXTENSION TUBE,  
& METAL TRANSITION BOX**

**DETAIL A  
SCALE 3 : 1**


**DETAIL B  
SCALE 3 : 1**

**DETAIL C  
SCALE 3 : 1**

**FULL SECTION  
SCALE 1:1**

**NOTES:**

1. STRUCTURAL ELEMENTS (PLYWOOD, RAFTERS, DRYWALL ETC.) BY OTHERS & SHOWN FOR REFERENCE ONLY.
2. ALL TUBE JOINTS & SEAMS TAPED WITH 2" FOIL TAPE (NOT SHOWN).
3. DIMENSIONS IN BRACKETS ARE METRIC UNLESS OTHERWISE SPECIFIED.
4. 6" MIN CLEARANCE SHOULD BE MAINTAINED FROM ALL SOLATUBE COMPONENTS AND OTHER PLENUM COMPONENTS.
5. 30" MIN. HEIGHT NEEDED FOR TRANSITION BOX.
6. ONE (1) SOFTLIGHT EXTENSION TUBE PER DAYLIGHTING SYSTEM. MUST INSTALL AS FINAL EXTENSION TUBE PRIOR TO THE BOTTOM (ANGLE) TUBE.

UNLESS OTHERWISE SPECIFIED:		SOLATUBE INTERNATIONAL, INC. COPYRIGHT 2013 WWW.SOLATUBE.COM		 2215 DAK ROOSE WAY COSTA MESA, CALIFORNIA 92626-5341 PH (714) 977-4400	
DIMENSION TOLERANCE FRACTIONS ± 1/4" DASH MILLIMETER X ± .1 [X] ± 2.5 XX ± .06 [XX] ± 1.5		DRAWN BY STEVENS	DATE 3/21/19	TITLE: <b>330 DS-C CURB CAP SUSPENDED CEILING</b>	
MATERIAL -	CHECKED BY -	DATE -	DATE -	SIZE <b>D</b>	DWG. NO. <b>330DS-C-DA-FC-AK-ES-TM-D</b>
FINISH -	APPROVED BY -	DATE -	DATE -	REV <b>2</b>	SCALE: 1:1
DO NOT SCALE DRAWING				SHEET 1 OF 1	