


- NOTES:
1. STRUCTURAL ELEMENTS (PLYWOOD, RAFTERS, DRYWALL ETC.) BY OTHERS & SHOWN FOR REFERENCE ONLY.
 2. ALL TUBE JOINTS & SEAMS TAPED WITH 2" FOIL TAPE (NOT SHOWN).
 3. DIMENSIONS IN BRACKETS ARE METRIC UNLESS OTHERWISE SPECIFIED.
 4. 6" MIN CLEARANCE SHOULD BE MAINTAINED FROM ALL SOLATUBE COMPONENTS AND OTHER PLENUM COMPONENTS.

UNLESS OTHERWISE SPECIFIED:		SOLATUBE INTERNATIONAL, INC. COPYRIGHT 2013 WWW.SOLATUBE.COM		 <small>2015 DAK ROOFWAY 2014, CALIFORNIA 92081-8341 PH (760) 977-4400</small>	
DIMENSION TOLERANCE FRACTIONS ± 1/4" DASH MILLIMETER X ± .1 [X] ± 2.5 XX ± .06 [XX] ± 1.5		DRAWN BY STEVENS		DATE 11/27/18	
MATERIAL -		CHECKED BY -		DATE -	
FINISH -		APPROVED BY -		DATE -	
DO NOT SCALE DRAWING		-		-	
TITLE: 330 DS (21") CURB CAP PITCHED ROOF-OPEN CEILING				SIZE	REV
DWG. NO. 330DS-O-DA-FCp-AK				SCALE: 1:1	2
SHEET 1 OF 1					