

**SOLATUBE 750DS-C-DAI-FC-AK-ES-TM
(21 IN / 530 MM)
CURB CAP
SUSPENDED CEILING WITH
& METAL TRANSITION BOX**

**DETAIL A
SCALE 3 : 1**


**DETAIL B
SCALE 3 : 1**

**DETAIL C
SCALE 3 : 1**

**FULL SECTION
SCALE 1:1**

NOTES:

1. STRUCTURAL ELEMENTS (PLYWOOD, RAFTERS, DRYWALL ETC.) BY OTHERS & SHOWN FOR REFERENCE ONLY.
2. ALL TUBE JOINTS & SEAMS TAPED WITH 2" FOIL TAPE (NOT SHOWN).
3. DIMENSIONS IN BRACKETS ARE METRIC UNLESS OTHERWISE SPECIFIED.
4. 6" MIN CLEARANCE SHOULD BE MAINTAINED FROM ALL SOLATUBE COMPONENTS AND OTHER PLENUM COMPONENTS.
5. 30" MIN. HEIGHT NEEDED FOR TRANSITION BOX.
6. ONE (1) SOFTLIGHT EXTENSION TUBE PER DAYLIGHTING SYSTEM. MUST INSTALL AS FINAL EXTENSION TUBE PRIOR TO THE BOTTOM (ANGLE) TUBE.

UNLESS OTHERWISE SPECIFIED:		SOLATUBE INTERNATIONAL, INC. COPYRIGHT 2013 WWW.SOLATUBE.COM		 2010 DAK ROOPE WAY COSTA MESA, CALIFORNIA 92626-5341 PH (714) 977-4400	
DIMENSION TOLERANCE FRACTIONS ± 1/4" DASH MILLIMETER X ± .1 [X] ± 2.5 XX ± .06 [XX] ± 1.5		DRAWN BY STEVENS		DATE 3/21/19	
MATERIAL -		CHECKED BY -		DATE -	
FINISH -		APPROVED BY -		DATE -	
DO NOT SCALE DRAWING		-		-	
TITLE: 750 DS-C CURB CAP SUSPENDED CEILING				REV 2	
DWG. NO. 750DS-C-DAI-FC-AK-TM				SCALE: 1:1	
SHEET 1 OF 1					