Solatube® Brighten Up® Series Rooftop Fire Glazing

Solatube® 160 DS / 290 DS / 300 DS*

(Please refer to the Brighten Up Series main set of instruction (P/N: 951780) to complete the installation.)

* 300 DS SolaMaster

Parts List	Quantity
1	Rooftop Fire Glazing	(1)
2	Tube Clips	(4)

Required Tools:
Screw Gun with Phillips Head
5/8 in (15.9mm) Hex Head bit
Required Safety Equipment

Please Note: The Solatube Rooftop Fire Glazing must be used in conjunction with the Solatube Dome Edge Protection Band.

For the most current Installation Instructions, please visit www.solatube.com/instructions

Part No. 951284 v1.0

Solatube® Brighten Up® Series Rooftop Fire Glazing

1 Remove tube clips and dome ring from top tube.
Remove tube ring and set aside for later use.

2 Install provided metal clips into notches on top tube.
Pull up on clip and apply foil tape to secure.

Foil tape

Apply pressure to tape for proper bonding

3 Insert Top Tube and Rooftop Fire Glazing

Insert top tube into flashing

Latch clips over flashing

Insert rooftop fire glazing into flashing and top tube

Insert tube ring on top fire glazing and flashing

Dome screw

Fasten to flashing with dome screws (provided with dome fastener kit)

Complete installation process, including dome and tube installation per Solatube Brighten Up Series Installation Instructions P/N: 951780.
Please Note: The Solatube Rooftop Fire Glazing must be used in conjunction with the Solatube Dome Edge Protection Band to meet the prescriptive method of option 1 of IBC 708A.2.1.

If local jurisdiction official needs assistance in understanding prescriptive acceptance, please contact Cal Fire or your Office of the State Fire Marshal as they can step them through the prescriptive process.

For the most current Installation Instructions, please visit www.solatube.com/instructions

Part No. 951284 v1.0